



LUMINARIAS DE SUPERFICIE

SURFACE MOUNTED LUMINAIRES


Apliques de techo / Ceiling lights



T5

L
Longitud
Length

SWD 124	1 x 24 / 1 x 14 W	☐ 585 mm
SWD 139	1 x 39 / 1 x 21 W	☐ 885 mm
SWD 154	1 x 54 / 1 x 28 W	☐ 1.185 mm
SWD 180	1 x 80 / 1 x 49 / 1 x 35 W	☐ 1.485 mm



SWD 224	2 x 24 / 2 x 14 W	☐ 585 mm
SWD 239	2 x 39 / 2 x 21 W	☐ 885 mm
SWD 254	2 x 54 / 2 x 28 W	☐ 1.185 mm
SWD 249	2 x 49 / 2 x 35 W	☐ 1.485 mm



Módulos dobles / Doubles modules

SWD 139.2	1 x 39 + 1 x 39 / 1 x 21 + 1 x 21 W	☐ 1.650 mm
SWD 154.2	1 x 54 + 1 x 54 / 1 x 28 + 1 x 28 W	☐ 2.250 mm
SWD 180.2	1 x 80 + 1 x 80 / 1 x 49 + 1 x 49 / 1 x 35 + 1 x 35 W	☐ 2.850 mm



SWD 239.2	2 x 39 + 2 x 39 / 2 x 21 + 2 x 21 W	☐ 1.868 mm
SWD 254.2	2 x 54 + 2 x 54 / 2 x 28 + 2 x 28 W	☐ 2.468 mm
SWD 249.2	2 x 49 + 2 x 49 / 2 x 35 + 2 x 35 W	☐ 3.068 mm




[Luminarias de superficie en perfil de aluminio, completas con elementos de fijación directa a techo. Difusor de metacrilato opal. Opción con equipos electrónicos regulables ER.

Acabados en gris metalizado, blanco B y negro mate N]

[Aluminium surface-mounting luminaires, complete with direct ceiling mounting elements. Opal metacrylate diffuser. ER dimmer available as an option.

Finished in metallic grey, white B and matt black N]



Con equipo electrónico multipotencia ☐.
Incluido tubo fluorescente T5 luz 840, el de mayor potencia.
With electronic multipower ☐ control gear.
T5 840 fluorescent tube included, maximum power lamp.