

Sistema colgante
Pendant system

Monolit



[Módulos en perfil de aluminio.

Difusor metacrilato opal directo y prismático indirecto.

Opciones con equipos electrónicos y regulables ER para T5.


Acabados en gris metalizado, blanco B y negro mate N]

[Aluminium profile modules.


Opal methacrylate (direct) and prismatic (indirect) diffuser.

Available ER dimmers for T5 models.



Finished in metallic grey, white B and matt black N]



Detalle cobertura luminaria
Detail of cover luminaire



Tapa luz directa
Direct light cover



SISTEMA COLGANTE LUZ DIRECTA / INDIRECTA

PENDANT DIRECT / INDIRECT LIGHTING SYSTEM



Módulos luz continua / Continuous lighting modules

	T5	L Longitud Length
MT 224	2 x 24 / 2 x 14 W	940 mm
MT 254	2 x 54 / 2 x 28 W	1520 mm
MT 280	2 x 80 / 2 x 49 / 2 x 35 W	1820 mm

Con equipo electrónico multipotencia control gear
With electronic multipower control gear

OPCIÓN LUZ DIRECTA

DIRECT LIGHT OPTION

Mediante accesorio TAPA (sustituye al sistema de cobertura superior de la luminaria) / The COVER accessory replaces the upper cover of the luminaire



MTT 940	Tapa LUZ DIRECTA / DIRECT LIGHT cover	940 mm
MTT 1520	Tapa LUZ DIRECTA / DIRECT LIGHT cover	1520 mm
MTT 1820	Tapa LUZ DIRECTA / DIRECT LIGHT cover	1820 mm

L
Longitud
Length