

Sistema empotrable
Recessed system

Blok Line



SISTEMA LINEAL DE EMPOTRAR

RECESSED LINEAR SYSTEM

Módulos luz continua / Continuous lighting modules



T 5



Longitud
Leight

LB 224 2 x 24 / 2 x 14 W

▣ 680 mm

LB 254 2 x 54 / 2 x 28 W

▣ 1280 mm

LB 249 2 x 49 / 2 x 35 W



▣ 1580 mm

Con equipo electrónico multipotencia ▣
With electronic multipower ▣ control gear

Bajo demanda se suministran módulos dobles
de 2560 mm y 3160 mm. Consultar
Double modules (2560 mm and 3160 mm) can be
built to order. Ask for details



En cortes longitudinales añadir 10 mm por línea
Altura mínima para empotrar 100 mm
Longitudinal ceiling cuts add 10 mm by line
Minimum height to recess 100 mm



[Módulos compuestos de perfil y tapa registrable de aluminio con seguro anticaída y difusor metacrilato opal. Elementos de fijación a falso techo incorporados.

Opciones con equipos electrónicos regulables ER.

Acabados en gris metalizado, blanco B y negro mate N]

[Aluminium profile and inspection cover with safety clip and opal methacrylate diffuser.

Includes mounting elements for false ceiling installations.

ER dimmer available as an option.

Finished in metallic grey, white B and matt black N]