



SISTEMA COLGANTE DE LUZ DIRECTA / INDIRECTA

PENDANT DIRECT / INDIRECT LIGHTING SYSTEM

Módulos luz continua / Continuous lighting modules

		T5		L	
		Directo / Direct	Indirecto / Indirect	Longitud / Length	
		HAC 424	2 x 24 / 2 x 14 + 2 x 24 / 2 x 14 W		680 mm
		HAC 454	2 x 54 / 2 x 28 + 2 x 54 / 2 x 28 W		1280 mm
		HAC 449	2 x 49 / 2 x 35 + 2 x 49 / 2 x 35 W		1580 mm
		HAC 224 D	2 x 24 / 2 x 14 + 1 x 24 / 1 x 14 W		680 mm
		HAC 254 D	2 x 54 / 2 x 28 + 1 x 54 / 1 x 28 W		1280 mm
		HAC 249 D	2 x 49 / 2 x 35 + 1 x 49 / 1 x 35 W		1580 mm
		HAC 224 I	1 x 24 / 1 x 14 + 2 x 24 / 2 x 14 W		680 mm
		HAC 254 I	1 x 54 / 1 x 28 + 2 x 54 / 2 x 28 W		1280 mm
		HAC 249 I	1 x 49 / 1 x 35 + 2 x 49 / 2 x 35 W		1580 mm
		HAC 224	1 x 24 / 1 x 14 + 1 x 24 / 1 x 14 W		680 mm
		HAC 254	1 x 54 / 1 x 28 + 1 x 54 / 1 x 28 W		1280 mm
		HAC 249	1 x 49 / 1 x 35 + 1 x 49 / 1 x 35 W		1580 mm
		T5		L	
		Directo / Direct		Longitud / Length	
		HAD 224	2 x 24 / 2 x 14 W		680 mm
		HAD 254	2 x 54 / 2 x 28 W		1280 mm
		HAD 249	2 x 49 / 2 x 35 W		1580 mm

Con equipo electrónico multipotencia .
Bajo demanda se suministran módulos de medida doble. Consultar
With electronic multipower control gear
Double modules can be built to order. Ask for details

[Módulos en perfil de aluminio. Difusor de metacrilato opal para luz directa y luz indirecta. Doble encendido con control independiente de la luz directa e indirecta. Opciones con equipos electrónicos regulables ER. Acabados en gris metalizado, blanco B y negro mate N]

[Aluminium profile modules. Opal metacrylate for direct and indirect light diffuser. Separate direct/indirect ON-OFF control. ER dimmer available as an option. Finished in metallic grey, white B and matt black N]

