



[Downlights de empotrar. Cuerpo metálico y cristal térmico mate. Sustitución de lámpara mediante extracción del aparato.

Acabados en gris metalizado, blanco B y negro N]

[Recessed downlights. Metal body with matt heat-resistant cover glass. Lamps replaceable by removing fixture.

Finished in metallic grey, white B and black N]

MINI DOWNLIGHTS

MINI DOWNLIGHTS

Empotrables Baja Tensión / Recessed low voltage downlights

 GY 6,35
BI-PIN

CEL 50 1 x 50 W máx. - 12 V **LxA**
Medidas
Measurements
90 x 90 mm



Con transformador electrónico incluido
Electronic transformer supplied

Asimétrico / Asymmetric

CEL 50 AS 1 x 50 W máx. - 12 V **LxA**
Medidas
Measurements
90 x 90 mm



Con transformador electrónico incluido
Electronic transformer supplied

Empotrables 230 V / 230 V recessed

 G-9
H-PIN

CEL 230 1 x 40 W máx. **LxA**
Medidas
Measurements
90 x 90 mm



Asimétrico / Asymmetric

CEL 230 AS 1 x 40 W máx. 90 x 90 mm



ACCESORIOS

ACCESSORIES

CCA 1 Caja de empotrar en pared de obra
Wall recess casing

