



LUMINARIAS DE BAJA LUMINANCIA

LOW LUMINANCE LUMINAIRES

Empotrables polivalentes / Multipurpose recess luminaires



medidas
measurements
LxA / LxW

PAR 414 4 x 14 W

595x595mm



PAR 424 4 x 24 W

595x595mm

PAR 314 3 x 14 W

595x595mm



PAR 324 3 x 24 W

595x595mm

PAR 254 2 x 54 / 2 x 28 W 1197x297mm



Con equipo electrónico y electrónico multipotencia .
Lámparas fluorescentes T5 luz 840 incluidas, el de mayor potencia
With electronic and electronic multipower control gear
T5 840 fluorescent tubes included, maximum power lamp



[Luminarias de empotrar y altura reducida con bandeja metálica porta-ópticas de muy baja luminancia.

Borne de conexión rápida.

Opciones con equipos electrónicos regulables ER.

Acabados en blanco y en gris GM]

[Slimline recessed luminaire with ultra low-luminance optic tray.

Quick-connect terminal. ER dimmer available as an option.

Finished in white and grey GM]

ACCESORIOS

ACCESSORIES

Juego de soportes para luminarias en techos recortables o perfil oculto
Set of brackets for luminaires mounted in cut-out or concealed grid ceilings

SPL Suministro 4 Uds. / 4 units

PARA TECHOS RECORTABLES (escayola u otros)
EFECTUAR EL HUECO DESCANTANDO 17 mm
FOR CUT-OUT CEILINGS (plaster and other materials)
MAKE RECESS SHALLOWER BY 17 mm

