



[Luminaria aplique de pared en perfil de aluminio, completa con elementos de fijación a pared. Difusor de policarbonato opal.



Opciones con equipos electrónicos regulables ER y kit de emergencia integrado EM.

Acabados en gris metálico, blanco B y negro mate N]

[Wall-mounted aluminium luminaire with wall mounting elements. Opal polycarbonate diffuser.

ER dimmer and emergency kit available as an option EM.

Finished in metallic grey, white B and matt black N]



LUMINARIAS LUZ DIRECTA O INDIRECTA

DIRECT OR INDIRECT LUMINAIRES

Apliques pared / Wall lights



T5

L
Longitud
Length

ADA 124 1 x 24 / 1 x 14 W

585 mm

ADA 139 1 x 39 / 1 x 21 W

885 mm

ADA 154 1 x 54 / 1 x 28 W

1185 mm

ADA 180 1 x 80 / 1 x 49 / 1 x 35 W

1485 mm

Con equipo electrónico multipotencia.

Incluido tubo fluorescente T5 luz 840, el de mayor potencia.

Opción kit de emergencia integrado, excepto 24/14 W

With electronic multipower control gear

T5 840 fluorescent tube included, maximum power lamp.

Emergency kit available as an option, except 24/14 W

Bajo demanda se suministran módulos a medida.

Consultar

Special measures modules can be built to order.

Ask for details

