



Luminarias / Luminaires



Cel



DOWNLIGHTS DE LUZ RASANTE


FLOOR LIGHT DOWNLIGHTS

Empotrables LED / LED recessed

	Flujo Luz Light output	Consumo Consumption	Temperatura color disponible *K Available color temperature *K
CEL 4.60 AS	250 lm	4,5W	6.000°K
CEL 4.40 AS	210 lm	4,5W	4.000°K
CEL 4.30 AS	190 lm	4,5W	3.000°K

Downlights de empotrar con tecnología LED de alta eficiencia y luminosidad. Vida útil superior a las 50.000 h con mantenimiento de flujo al 70%. Diseñados para aplicaciones de luz asimétrica en instalaciones de techo y luz rasante en instalaciones de pared.
Con driver electrónico 350 mA incluido.

*Recessed LED downlights high performance lumen output. 50.000 hrs operating life with 70% lumen maintenance. Designed for false ceiling and wall asimetric applications.
350 mA electronic driver included.*



ACCESORIOS / ACCESSORIES
CCA FA: Caja de empotrar en muro, con espacio para el driver. Recessed in-wall box, with space for driver.

ACABADOS / FINISHES
B GM N

DIRECCION LUZ / LIGHT DIRECTION
[Icon of a light beam]

TECNOLOGÍA / TECHNOLOGY
ONE ROW LINEAR MATRIX

