



Luminarias / Luminaires



Ada LED



LUMINARIAS LED PARA CARRIL TRIFÁSICO

THREE PHASE TRACK LED LUMINAIRES

Superficie / Surface

	Flujo luz Light output	Consumo Consumption	Temperatura color disponible %K Available color temperature %K	CRI Disponibles Available CRI	L - Longitud L - Length
ADA 30 CT	3.500 lm	30W	3.000/4.000°K	CRI> 80	852 mm
ADA 43 CT	4.700 lm	43W	3.000/4.000°K	CRI> 80	1.132 mm
ADA 53 CT	5.950 lm	53W	3.000/4.000°K	CRI> 80	1.413 mm
ADA 63 CT	7.150 lm	63W	3.000/4.000°K	CRI> 80	1.693 mm

Con equipo electrónico incorporado.
Opción equipo electrónico regulable (DALI, Touch&Dimm).
Precisa carril dali.
Difusor opal.

*With electronic control gear built-in.
Available as an option electronic dimmable gear (Dali, Touch&Dimm).
Dali track is required.
Opal diffuser.*

COMPOSICIÓN DE REFERENCIAS / REFERENCE PLANNING

.30 3.000°K CRI>80 **.ER** electrónico regulable
.40 4.000°K CRI>80 **dimmbable**

EJEMPLO DE REFERENCIA / REFERENCE EXAMPLE:

ADA 30.30 CT GM: 30W 3.500 lm 3.000°K
Gris metalizado / Metallic grey

ACABADOS / FINISHES



DIRECCION LUZ / LIGHT DIRECTION



TECNOLOGÍA / TECHNOLOGY

