



Luminarias / Luminaires

Proyector Spotlight

Serie PHS



PROYECTOR LED DE CARRIL TRIFÁSICO O SUPERFÍCIE
THREE PHASE TRACK OR SURFACE MOUNTING LED SPOTLIGHT


	Flujo luz Light output	Temperatura color disponible °K Available color temperature °K	CRI Disponibles Available CRI
PHS 12	1.500 lm	2.700/3.000/4.000°K	CRI> 80/90
PHS 35	2.000 lm	2.700/3.000/4.000°K	CRI> 80/90
PHS 38	2.800 lm	2.700/3.000/4.000°K	CRI> 80/90
PHS 45	3.300 lm	2.700/3.000/4.000°K	CRI> 80/90
PHS 48	4.300 lm	2.700/3.000/4.000°K	CRI> 80/90

Con driver electrónico y sistema de disipación activa
Opción equipo electrónico regulable (DALI y Push&Dimm)
Precisa carril dali. Opción cristal mate 180°.
Ópticas disponibles 45° (serie), 25° y 12° (opcional).
Opción versión de techo (.BS).


With electronic control driver and active cooling system
Electronic dimmable drivers available (Dali and Push&Dimm)
Dali track is required. Optional matt glass 180°.
Available 45° round louvre, 25° and 12° (as an option).
Ceiling support for surface mounting version available (.BS).

Consultar tabla de potencias/consumos actualizados en www.castanweb.com/watts.html
See actual power consumptions on www.castanweb.com/watts.html

VERSIÓN CARRIL TRIFÁSICO /
THREEPHASE VERSION



VERSIÓN DIRECTO A TECHO /
SURFACE MOUNTING VERSION



COMPOSICIÓN DE REFERENCIAS / REFERENCE PLANNING

.27 2.700°K CRI>80	.930 3.000°K CRI>90	.CEM Cristal mate / Matt glass
.30 3.000°K CRI>80	.940 4.000°K CRI>90	.CT Carril trifásico / Threephase adapter
.40 4.000°K CRI>80		.BS Base a techo / Ceiling mounting
		.ER Regulable / Dimmable

EJEMPLO DE REFERENCIA / REFERENCE EXAMPLE:

PHS 35.930 CT GM: 12W 1.500 lm 3000° K CRI > 90

*Lumens y potencias referidos a 4.000°K CRI 80 / Lumens para 3.000°K -8% / Para CRI 90 -25%
Power and lumen output referred to 4.000°K CRI 80 / Estimated lumens for 3.000°K -8% / For CRI 90 -25%.

ACABADOS / FINISHES	DIRECCION LUZ / LIGHT DIRECTION	TECNOLOGÍA/ TECHNOLOGY
B GM N		