



Luminarias de exterior / Outdoor luminaires



# RoundL



## APLIQUES DE TECHO/PARED EXTERIOR LED OUTDOOR CEILING/WALL MOUNTING LED LUMINAIRES

### Aplique de pared / Wall luminaires

|       | Flujo luz<br>Light output | Consumo<br>Consumption | Temperatura color disponible °K<br>Available color temperature °K | CRI Disponibles<br>Available CRI |
|-------|---------------------------|------------------------|-------------------------------------------------------------------|----------------------------------|
| RL 12 | 1.100 lm                  | 11W                    | 3.000/4.000°K                                                     | CRI> 80                          |
| RL 20 | 2.000 lm                  | 20W                    | 3.000/4.000°K                                                     | CRI> 80                          |

Fabricado íntegramente en aluminio anodizado o acero inoxidable 316 A4 (marino).  
Con driver electrónico incorporado. Óptica 180°.  
Cristal anticondensación mate.  
Elementos de fijación y cierre (tornillería) de acero inox 316 A4.

*Made entirely with anodized aluminium or Stainless steel 316 A4 (marine installations).  
Electronic driver built-in. 180° optic.  
Not condensation matt glass supplied.  
Stainless steel 316 A4 screws.*

### COMPOSICIÓN DE REFERENCIAS / REFERENCE PLANNING

- .30 3.000°K CRI>80
- .40 4.000°K CRI>80

### EJEMPLO DE REFERENCIA / REFERENCE EXAMPLE:

RL 20.30 INX: 20W 3.000°K 2.000 lm  
Acero inox / Stainless steel

### ACABADOS / FINISHES



### DIRECCION LUZ / LIGHT DIRECTION



### TECNOLOGÍA/ TECHNOLOGY



IP 67

